

2023 Rolla ANSWER KEY

1. Remove O-rings by hand or with the _____ tool provided in the service kit.
 - A. Correct
 - B. Small
 - C. **Pick SOF 54**
2. DO NOT submerge the _____ Module during turn-around maintenance.
 - A. **Alarm SOF 26**
 - B. RMS
 - C. Biopak
3. Christo-Lube and Dow/Molly Kote 111 are the only _____ approved for use in the apparatus.
 - A. Brands
 - B. **Lubricants SOF 55**
 - C. Greases
4. Never lubricate the outlet tube _____ or the _____ that sits between the Oxygen cylinder and the pressure regulator.
 - A. Washer or the seal
 - B. Washer or the O-ring
 - C. **O-ring or the Seal SOF 56**
5. The alarm (RMS) module will require _____ if any damage to the housing is discovered.
 - A. **Replacement SOF 59**
 - B. Inspection
 - C. Programming
6. If the flow does not meet the requirements of the _____ in the Benchman Manual the flow restrictor will need replacement.
 - A. Statements
 - B. Requirements
 - C. **Table SOF 60**
7. A good facemask seal is important to achieving full protection and _____.
 - A. Visibility
 - B. **Duration SOF 61**
 - C. Comfort
8. Personnel who intend to use protective breathing equipment in a _____ atmosphere must have the proper training, temperament, and experience.
 - A. **Dangerous SOF 62**
 - B. IDLH
 - C. Methane
9. A _____ user will significantly increase the chances of achieving an adequate face seal.
 - A. Well Trained
 - B. Steady Temperamental
 - C. **Clean Shaven SOF 63**
10. The ongoing effectiveness and reliability of any protective breathing equipment is dependent upon the user's standard of care in _____ the equipment.
 - A. Donning
 - B. **Maintaining SOF 64**
 - C. Washing